

Loft Hatch LEX 60 EI 30

Holder/Issued to

MidMade AB

Stationsgatan 1A, 931 31 Skellefteå, Sweden

Product description

Loft hatch LEX 60, attic hatch consisting of wood and insulated with stone wool and glass wool, maximum dimensions 730 × 1200 mm, fire resistance class EI 30.

The hatch includes a folding wood ladder on top.

Intended use

Fire separating hatch in attic building elements.

Trade name

LEX 60

Approval

The product satisfies the requirements set forth in chapter 8, 4 § 2 PBL, in respect to and under conditions stated in this type approval, and are therefore approved in accordance with the provisions of the following sections of Boverket Building Regulations (BBR), issued by the National Board of Housing, Building and Planning.

Fire resistance class EI 30

5:231

Associated documents

Assembly Instructions MidMade Loft ladder LEX, dated 0210.

Control

The factory production control (FPC) is monitored by an independent inspection body.

Control plan: Ref no. 210-12-0016 dated 2012-01-16, Inspection body: RISE Research Institutes of Sweden AB

When the building proprietor performs inspection at the building site, markings shall be checked to ensure that the correct products have been supplied and that they are used in accordance with the conditions in this type approval and associated documents. Further the product shall be accompanied by a manufacturer's assurance, certifying that the product has been manufactured in accordance with the documents on which this type approval is based.

Manufacturing place

Production control includes the following place:

MidMade AB, Hantverksvägen 2, 861 36 Timrå, Sweden

Marking

The product is to be marked at the factory. The marking consists of a sign/label on every product supplied and includes:

Holder	MidMade AB
Manufacturing place	Timrå
Product type designation	LEX 60
Consecutive manufacture no./date of production	nr/datum
Type approval number	0363/93
Fire resistance class	EI 30
Boverket's registered trade mark	†
RISE Accreditation number	1002
Certification body and Inspection body	RISE

Basis for approval

Report 4P08580 from SP Technical Research Institute of Sweden.
Description LEX60 730x1200, dated 2016-01-18

<i>Drawing no.</i>	<i>Dated</i>
100443	2015-08-24
100500	2015-10-08
100501	2015-10-08
100502	2015-10-08
100503	2015-10-08

Comments

The mineral wool used in the hatch, is supposed to fulfill the requirements for class A1 or A2-s1,d0 according to EN 13501-1.

Associated documents shall accompany the product or by other means be available to users of the product.

This type approval supersedes the previous type approval with the same number dated 2018-10-01.

Validity

Valid through 2026-12-13.

Validity of this type approval can be verified on our website.

The validity of this type approval expires when the type approved product with the intended use according to this type approval shall be CE-marked according to the Construction Products Regulation (EU) 305/2011.

Martin Tillander

This is a translation from the Swedish original document. In the event of any dispute as to its content, the Swedish text shall take precedence.